

# Tech Sheet Fabric Guard Fabric Protector

Toll Free Customer Support (800) 877-6282

Fax Orders to (951) 493-1815 www.mark-v.com

# **Product Description:**

Unlike other retail and commercial fabric protectors, Fabric Guard's polymer formula is drawn in and around each fiber shaft. The polymer then cures. This is not just a coating that sits on top of the fabric. It actually penetrates each fiber and cures to create an impenetrable bond.

This not only provides optimum protection but also lubricates fibers. Lubricating the fibers retards the normal rate of abrasion that causes them to fray. Fraying is what causes the fabrics to fade and loose their brightness. So, Fabric Guard keeps the fabrics looking bright and like new.

Fabric Guard is unique in that it repels both water-based and oil based staining. Most products are just water repellents. They only repel water-based items (cola, tea, coffee). If an oily substance gets on the fabric, it will easily penetrate and stain. Our unique formula repels both types of soils, which keeps carpets cleaner and easier to clean.

Fabric Guard is a unique water-based formula with zero VOC's. It surpasses all State and Federal regulations. Once cured onto the fabric, the product is completely inert and hypoallergenic. So, it won't cause a rash or skin irritation.

Use Fabric Guard for protecting all fabrics, carpets, seating etc., in autos, boats, aircraft and motor home applications.

# Advantages:

- Repels both water and oil based stains (Coffee, Tea, Soda, Motor oil, etc.)
- Protects fabric from fraying
- Water-based formula
- Product contains zero VOCs
- Safe on all fabrics
- Easy to use and effective
- Exceeds all State and Federal regulations

### Part Numbers:

- 1 gallon bottle # 16-114
- 5 gallon tighthead # 16-115
- 55 gallon plastic drum # 16-118

### **Directions:**

- 1. Carpets and fabric should be clean and dry prior to applying Fabric Guard.
- 2. Spray product liberally being careful to apply product evenly onto the surface.
- 3. Brush with a soft brush to make sure product is evenly distributed and fabric is wet with product.
- 4. Allow product to dry for 2 hours.
- 5. Once product is dry, vehicle can be used. Product will take approximately 24 hours to fully cure and provide full protection from staining.



(800) 877-6282

Appearance Protection Systems for Auto, Marine and Air Mark V Products 400 El Sobrante Rd. Corona, CA 92879